


# Monolithic Dual Switching Diodes



**MMBD2835LT1**  
**MMBD2836LT1**



CASE 318-08, STYLE 12  
SOT- 23 (TO-236AB)

## MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Reverse Voltage MMBD2835LT1	$V_R$	35	Vdc
MMBD2836LT1		75	
Forward Current	$I_F$	100	mAdc

## THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Total Device Dissipation FR-5 Board <sup>(1)</sup>	$P_D$	225	mW
$T_A = 25^\circ\text{C}$			
Derate above $25^\circ\text{C}$		1.8	mW/ $^\circ\text{C}$
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	556	$^\circ\text{C}/\text{W}$
Total Device Dissipation	$P_D$	300	mW
Alumina Substrate, <sup>(2)</sup> $T_A = 25^\circ\text{C}$			
Derate above $25^\circ\text{C}$		2.4	mW/ $^\circ\text{C}$
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	417	$^\circ\text{C}/\text{W}$
Junction and Storage Temperature	$T_J, T_{stg}$	-55 to +150	$^\circ\text{C}$

## DEVICE MARKING

MMBD2835LT1 = A3X; MMBD2836LT1=A2X


## ELECTRICAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$ unless otherwise noted) ( EACH DIODE )

Characteristic	Symbol	Min	Max	Unit
<b>OFF CHARACTERISTICS</b>				
Reverse Breakdown Voltage( $I_R = 100 \mu\text{Adc}$ ) MMBD2835LT1	$V_{(BR)}$	35	—	Vdc
MMBD2836LT1		75	—	
Reverse Voltage Leakage Current ( $V_R = 30 \text{ Vdc}$ )	$I_R$	—	100	nAdc
( $V_R = 50 \text{ Vdc}$ )	MMBD2835LT1	—	100	
MMBD2836LT1		—	100	
Diode Capacitance ( $V_R = 0$ , $f = 1.0 \text{ MHz}$ )	$C_T$	—	4.0	pF
Forward Voltage( $I_F = 10 \text{ mAdc}$ )	$V_F$	—	1.0	Vdc
( $I_F = 50 \text{ mAdc}$ )		—	1.0	
( $I_F = 100 \text{ mAdc}$ )		—	1.2	
Reverse Recovery Time( $I_F = I_R = 10 \text{ mAdc}$ , $I_{R(\text{REC})} = 1.0 \text{ mAdc}$ ) (Figure 1)	$t_{rr}$	—	4.0	ns

1. FR-5 =  $1.0 \times 0.75 \times 0.062$  in.

2. Alumina =  $0.4 \times 0.3 \times 0.024$  in. 99.5% alumina.


## MMBD2835LT1 MMBD2836LT1



- Notes:
1. A 2.0 kΩ variable resistor adjusted for a Forward Current ( $I_F$ ) of 10mA.
  2. Input pulse is adjusted so  $I_{R(\text{peak})}$  is equal to 10mA.
  3.  $t_p \gg t_{rr}$


**Figure 1. Recovery Time Equivalent Test Circuit**

### CURVES APPLICABLE TO EACH CATHODE



$V_F$ , FORWARD VOLTAGE (VOLTS)

**Figure 2. Forward Voltage**



$V_R$ , REVERSE VOLTAGE (VOLTS)

**Figure 3. Leakage Current**



$V_R$ , REVERSE VOLTAGE (VOLTS)

**Figure 4. Capacitance**