

UHF variable capacitance diode

FEATURES

- Excellent linearity
- Excellent matching to 2% DMA
- Ultra small plastic SMD package
- C28: 2.1 pF; ratio: 9
- Low series resistance.


APPLICATIONS

- Electronic tuning in UHF television tuners
- Voltage controlled oscillators

DESCRIPTION

The BB179B is a planar technology variable capacitance diode, in a SOD523 (SC-79) package. The excellent matching performance is achieved by gliding matching and a direct matching assembly procedure.

BB 179B

SOD523 SC-79


LIMITING VALUES In accordance with the Absolute Maximum Rating System (IEC 134).

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
V_R	continuous reverse voltage		—	30	V
V_{RM}	peak reverse voltage	in series with a 10 kΩ resistor	—	35	V
I_F	continuous forward current		—	20	mA
T_{stg}	storage temperature		-55	+150	°C
T_j	operating junction temperature		-55	+125	°C

ELECTRICAL CHARACTERISTICS $T_j=25^\circ\text{C}$ unless otherwise specified.

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	TYP.	UNIT
I_R	reverse current	$V_R = 30 \text{ V}$; see Fig.2	—	—	10	nA
		$V_R = 30 \text{ V}$; $T_j = 85^\circ\text{C}$; see Fig.2	—	—	200	nA
r_s	diode series resistance	$f = 470 \text{ MHz}$; V_R is the value at which $C_d = 9 \text{ pF}$	—	0.6	0.75	Ω
C_d	diode capacitance	$V_R = 1 \text{ V}$; $f = 1 \text{ MHz}$; see Figs 1 and 3	18.22	—	20	pF
		$V_R = 28 \text{ V}$; $f = 1 \text{ MHz}$; see Figs 1 and 3	1.9	—	2.25	pF
$\frac{C_{d(1V)}}{C_{d(2V)}}$	capacitance ratio	$f = 1 \text{ MHz}$	—	1.27	—	
$\frac{C_{d(1V)}}{C_{d(28V)}}$	capacitance ratio	$f = 1 \text{ MHz}$	8.45	—	10	
$\frac{C_{d(25V)}}{C_{d(28V)}}$	capacitance ratio	$f = 1 \text{ MHz}$	—	1.05	—	
$\frac{\Delta C_d}{C_d}$	capacitance matching	$V_R = 1 \text{ to } 28 \text{ V}$; in a sequence of 15 diodes(gliding)	—	—	2	%

SEMICONDUCTOR


BB 179B


Fig.1 Diode capacitance as a function of reverse voltage; typical values.




Fig.2 Reverse current as a function of junction temperature; maximum values.




Fig.3 Temperature coefficient of diode capacitance as a function of reverse voltage; typical values.

SEMICONDUCTOR