

GTM ELECTRONICS

SOD-323 Schottky Diodes

Part No.	Maximum Peak Reverse Voltage	IO @T _A = 25°C	IFSM	Maximum Reverse Current @T _A = 25°C		Maximum Forward Voltage @T _A = 25°C		Cj	Marking Code
				I _R	V _R	I _{FM}	V _{FM}		
	V	mA	A	uA	V	mA	V	pF	
GD103SD	40	350	1.5	5	30	200	0.6	5	S4
GD400SD	40	500	3	50	30	500	0.55	20	5F
GD401SD	30	200	3	100	30	200	0.5	40	5H
GD402SD	30	300	3	100	30	300	0.5	40	5K
GD411SD	40	500	3	30	10	10	0.3	20	5T
GD420SD	40	100	1	1	10	10	0.45	6	V5
GD421SD	40	100	1	30	10	100	0.55	6	V6
GD490SD	40	1000	3	100	30	1000	0.53	30	5D
GD491SD	25	1000	3	200	20	1000	0.45	30	5E
GD500SD	45	100	1	1	10	10	0.45	6	5A
GD501SD	45	100	1	30	10	100	0.55	6	5B
GD551SD	30	500	2	100	20	100	0.36	15	5C
GD751SD	40	30	0.2	0.5	30	1	0.37	2	7A
GDBAS40	40	200	0.6	0.2	30	40	1	5	43
GDBAS70	70	70	0.1	0.1	50	15	1	2	B1
GDBAT34	30	100	0.6	2	25	100	1	10	L3
GDBAT54	30	200	0.6	2	25	100	1	10	L4

量產	未量產	有樣品	工程實驗未產出
----	-----	-----	---------