




## GP202K

**SURFACE MOUNT, SWITCHING DIODE**  
**VOLTAGE 80V, CURRENT 0.1A**

### Description

The GP202K is designed for ultra high speed switching.

### Package Dimensions



REF.	Millimeter		REF.	Millimeter	
	Min.	Max.		Min.	Max.
A	2.70	3.10	G	1.90	REF.
B	2.40	2.80	H	1.00	1.30
C	1.40	1.60	K	0.10	0.20
D	0.35	0.50	J	0.40	-
E	0	0.10	L	0.85	1.15
F	0.45	0.55	M	0°	10°







### Absolute Maximum Ratings at TA = 25°C

Parameter	Symbol	Ratings	Unit
Junction Temperature	T <sub>j</sub>	+150	°C
Storage Temperature	T <sub>stg</sub>	-55 ~ +150	°C
Peak Reverse Voltage	V <sub>RM</sub>	80	V
DC Reverse Voltage	V <sub>R</sub>	80	V
Mean Rectifying Current	I <sub>O</sub>	100	mA
Peak Forward Current	I <sub>FM</sub>	300	mA
Peak Forward Surge Current (1uSec)	I <sub>FSM</sub>	4	A
Total Power Dissipation	P <sub>D</sub>	200	mW

### Electrical Characteristics (at TA = 25°C unless otherwise noted)

Parameter	Symbol	Min.	Max.	Unit	Test Conditions
Reverse Voltage	V <sub>R</sub>	80	-	V	I <sub>R</sub> =100uA
Forward Voltage	V <sub>F</sub>	-	1.2	V	I <sub>F</sub> =100mA
Reverse Current	I <sub>R</sub>	-	0.1	uA	V <sub>R</sub> =70V
Capacitance between terminals	C <sub>T</sub>	-	3.5	pF	V <sub>R</sub> =6V, f=1MHz
Reverse Recovery Time	T <sub>rr</sub>	-	4	nS	V <sub>R</sub> =6V, I <sub>F</sub> =5mA

## Characteristics Curve



**Important Notice:**

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of GTM.
- GTM reserves the right to make changes to its products without notice.
- GTM semiconductor products are not warranted to be suitable for use in life-support Applications, or systems.
- GTM assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.

**Head Office And Factory:**

- Taiwan:** No. 17-1 Tatung Rd. Fu Kou Hsin-Chu Industrial Park, Hsin-Chu, Taiwan, R. O. C.
- TEL : 886-3-597-7061 FAX : 886-3-597-9220, 597-0785
- China:** (201203) No.255, Jang-Jiang Tsai-Lueng RD. , Pu-Dung-Hsin District, Shang-Hai City, China
- TEL : 86-21-5895-7671 ~ 4 FAX : 86-21-38950165