


GDBAS16

SURFACE MOUNT, SWITCHING DIODE VOLTAGE 85V, CURRENT 250mA

Description

The GDBAS16 is designed for high-speed switching application in hybrid thick and thin-film circuits. The devices is manufactured by the silicon epitaxial planar process and packed in a plastic surface mount package.

Package Dimensions




Absolute Maximum Ratings at TA = 25°C

Parameter	Symbol	Ratings	Unit
Junction Temperature	T _j	+150	°C
Storage Temperature	T _{stg}	-65 ~ +150	°C
Reverse Voltage	V _R	85	V
Repetitive Reverse Voltage	V _{RRM}	85	V
Forward Current	I _O	250	mA
Repetitive Forward Current	I _{FM}	500	mA
Forward Surge Current (1ms)	I _{FSM}	1000	mA
Total Power Dissipation	P _D	225	mW

Electrical Characteristics (at TA = 25°C unless otherwise noted)

Characteristic	Symbol	Min.	Max.	Unit	Test Conditions
Reverse Breakdown Voltage	V _(BR)	85	-	V	I _R =100uA
Forward Voltage	V _F (1)	-	715	mV	I _F =1mA
	V _F (2)	-	855	mV	I _F =10mA
	V _F (3)	-	1000	mV	I _F =50mA
	V _F (4)	-	1250	mV	I _F =150mA
Reverse Current	I _R	-	1	uA	V _R =85V
Total Capacitance	C _T		2	pF	V _R =0, f=1MHz
Reverse Recovery Time	T _{rr}	-	6	nS	I _F =I _R =10mA, R _L =100Ω measured at I _R =1mA

Characteristics Curve

**Important Notice:**

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of GTM.
- GTM reserves the right to make changes to its products without notice.
- GTM semiconductor products are not warranted to be suitable for use in life-support Applications, or systems.
- GTM assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.

Head Office And Factory:

- **Taiwan:** No. 17-1 Tatung Rd. Fu Kou Hsin-Chu Industrial Park, Hsin-Chu, Taiwan, R. O. C.
TEL : 886-3-597-7061 FAX : 886-3-597-9220, 597-0785
- **China:** (201203) No.255, Jang-Jiang Tsai-Lueng RD. , Pu-Dung-Hsin District, Shang-Hai City, China
TEL : 86-21-5895-7671 ~ 4 FAX : 86-21-38950165