

GLBCX53 PNP SILICON EPITAXIAL TRANSISTOR


Description

The GLBCX53 is designed for use in driver stages of audio amplifiers and medium power general purpose amplification.

Features

- Collector-Emitter Voltage: $V_{CE0}=-80V$
- Complementary to GLBCP56

Package Dimensions



Absolute Maximum Ratings at $T_a = 25^\circ C$

Parameter	Symbol	Ratings	Unit
Junction Temperature	T_j	+150	$^\circ C$
Storage Temperature Range	T_{STG}	-65 ~ +150	$^\circ C$
Collector to Base Voltage	V_{CBO}	-100	V
Collector to Emitter Voltage	V_{CEO}	-80	V
Emitter to Base Voltage	V_{EBO}	-5	V
Collect Current(DC)	I_C	1	A
Total Power Dissipation	P_D	1.5	W

Electrical Characteristics ($T_a = 25^\circ C$)




Symbol	Min.	Typ.	Max.	Unit	Test Conditions
B_{VCBO}	-100	-	-	V	$I_C=-100\mu A, I_E=0$
B_{VCEO}	-80	-	-	V	$I_C=-1mA, I_B=0$
B_{VEBO}	-5	-	-	V	$I_E=-10\mu A, I_C=0$
I_{CBO}	-	-	-100	nA	$V_{CB}=-30V, I_E=0$
I_{EBO}	-	-	-100	nA	$V_{EB}=-5V, I_C=0$
* $V_{CE(sat)1}$	-	-	-500	mV	$I_C=-500mA, I_B=-50mA$
* $V_{BE(on)}$	-	-	-1000	mV	$I_C=-500mA, V_{CE}=-2V,$
* h_{FE1}	63	-	-		$V_{CE}=-2V, I_C=-5mA$
* h_{FE2}	63	-	250		$V_{CE}=-2V, I_C=-150mA$
* h_{FE3}	40	-	-		$V_{CE}=-2V, I_C=-500mA$
f_T	100	-	-	MHz	$V_{CE}=-5V, I_C=-10mA, f=100MHz$

* Pulse Test: Pulse Width $\leq 380\mu s$, Duty Cycle $\leq 2\%$

Classification Of h_{FE2}

Rank	A	B
Range	63 - 160	100 - 250

Characteristics Curve



Important Notice:

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of GTM.
- GTM reserves the right to make changes to its products without notice.
- GTM semiconductor products are not warranted to be suitable for use in life-support Applications, or systems.
- GTM assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.

Head Office And Factory:

- **Taiwan:** No. 17-1 Tatung Rd. Fu Kou Hsin-Chu Industrial Park, Hsin-Chu, Taiwan, R. O. C.
TEL : 886-3-597-7061 FAX : 886-3-597-9220, 597-0785
- **China:** (201203) No.255, Jang-Jiang Tsai-Lueng RD. , Pu-Dung-Hsin District, Shang-Hai City, China
TEL : 86-21-5895-7671 ~ 4 FAX : 86-21-38950165